



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

3M EPS200 Adhesive lined heat shrink tubing

Features:

3M 2:1 heat shrink tubing is supplied standard with a "dual-wall" construction. When exposed to the heat from a heat gun (roughly at 90°C), the inner layer begins to flow (just like a hot melt adhesive). When the tubing shrinks and subsequently cools down, the inner layer solidifies and forms a moisture barrier between the tubing and the component or wire. This provides a water-tight seal, protecting the connector and/or wire.

Dimensions

Part Number	Diameter	Mil Specification #	Manufacturer Part #
HS-EPS200-0125	1/8"	N/A	EPS200-1/8
HS-EPS200-025	1/4"	AMS-DTL-23053/4-201-0	EPS200-1/4
HS-EPS200-0375	3/8"	AMS-DTL-23053/4-202-0	EPS200-3/8
HS-EPS200-050	1/2"	AMS-DTL-23053/4-203-0	EPS200-1/2
HS-EPS200-075	3/4"	AMS-DTL-23053/4-204-0	EPS200-3/4
HS-EPS200-100	1"	AMS-DTL-23053/4-205-0	EPS200-1
HS-EPS200-150	1-1/2"	AMS-DTL-23053/4-206-0	EPS200-1-1/2