



A division of CSA Technical Solutions, LLC  
**1959 Hammondville Road, Pompano Beach, FL 33069**  
**Phone 954-978-0056 Fax 888-617-2010**  
[www.BuyHeatShrink.com](http://www.BuyHeatShrink.com)

## Abrasion Resistant Nylon Cable Sleeving

Our heavy duty abrasion resistant nylon sleeves have excellent cut through and abrasion resistance, yet can be cut with ordinary scissors. This Ultra Tight woven product is highly resistant to pressure leaks (will stop hose burst from spraying hot fluid). Our braided sleeving products meet the latest EN982 ISO norm 833 EN414 standard for "Line of Sight" operator protection; they are Halogen Free, MSHA approved and ROHS Compliant. These heavy duty nylon abrasion sleeves have a continuous use temperature of -60°C to 132°C (-60°F to 270°F) and a melt temperature of 260°C (500°F). They are self extinguishing, highly resistant to gasoline, automotive engine chemicals and most cleaning solvents. Available in sizes 5/8" to 3-3/4". Made in U.S.A.

### Features:

- Excellent cut through and abrasion resistance, yet can be cut with ordinary scissors
- Highly resistant to pressure leaks (will stop hose burst from spraying hot fluid)
- Ultra Tight woven product
- MSHA approved
- Meets the latest EN982 ISO norm 833 EN414 standard for "Line of Sight" operator protection
- Continuous use temperature of -60°C to 132°C (-60°F to 270°F) • Melt temperature of 260°C (500°F)
- Available in sizes 5/8" to 3-3/4".
- Packaged in spools of 100 ftt and 300 feet
- Halogen Free, ROHS compliant
- Self Extinguishing
- Resists Gasoline, Engine Chemicals & Cleaning Solvents
- Made in U.S.A.

### Dimensions

Part Number	Diameter	Nominal ID	Flat Width
BSABR-0625	5/8"	17	1.18
BSABR-075	3/4"	20	1.22
BSABR-078	7/8"	23	1.54
BSABR-100	1"	25	1.65
BSABR-116	1-1/16"	27	1.77
BSABR-125	1-1/4"	31	2.05
BSABR-1375	1-3/8"	36	2.24
BSABR-150	1-1/2"	40	2.6
BSABR-1625	1-5/8"	44	2.83
BSABR-175	1-3/4"	47	3.03
BSABR-2188	2-3/16"	55	3.5
BSABR-2375	2-3/8"	2 3/8"	3.82
BSABR-275	2-3/4"	2 3/4"	4.65

BSABR-3625	3-5/8"	3 5/8"	4.76
BSABR-375	3-3/4"	3 3/4"	5.87