



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Bentley Harris Expando PT PLUS | BuyHeatShrink

The patented Bentley Harris Plus treatment provides end users with a fray-resistant PET expandable braided sleeving that will not open up during installation or use. A hot knife is not required for use of this product. Rated for continuous use at temperatures up to 125°C.

Features:

- Excellent cut through and abrasion resistance
- Continuous use temperature of -70°C to 125°C (-103°F to 257°F)
- Expando PT Plus contains a patented fray resistant treatment.
- Melt temperature of 230°C (446°F)
- Expands up to three times its resting diameter
- Halogen Free, ROHS compliant
- Self Extinguishing
- Resists Gasoline, Engine Chemicals & Cleaning Solvents
- Braided from 10 mil polyethylene terephthalate (PET) monofilament yarns.
- Available in Black. Other Colors available

Dimensions

Part Number	Manufacturer Part Number (MPN/GTIN)	Diameter	Feet	Nominal Size	Expansion min	Expansion Max
BSBHPTP-0125	5101000303	1/8"	2000 FT/SPOOL	1/8"	3/32"	1/4"
BSBHPTP-025	5101000603	1/4"	1000 FT/SPOOL	1/4"	1/8"	3/8"
BSBHPTP-0375	5101001003	3/8"	500 FT/SPOOL	3/8"	3/16"	5/8"
BSBHPTP-050	5101001303	1/2"	500 FT/SPOOL	1/2"	1/4"	3/4"
BSBHPTP-075	5101001903	3/4"	500 FT/SPOOL	3/4"	1/2"	1 1/4"
BSBHPTP-125	5101003203	1-1/4"	250 FT/SPOOL	1 1/4"	3/4"	1 3/4"
BSBHPTP-175	5101004503	1-3/4"	250 FT/SPOOL	1 3/4"	1"	2 3/4"
BSBHPTP-200	5101005103	2"	250 FT/SPOOL	2"	1 1/4"	3"
BSBHPTP-250	5101006403	2-1/2"	200 FT/SPOOL	2 1/2"	1 1/2"	4 1/2"