



A division of CSA Technical Solutions, LLC  
**1959 Hammondville Road, Pompano Beach, FL 33069**  
**Phone 954-978-0056 Fax 888-617-2010**  
[www.BuyHeatShrink.com](http://www.BuyHeatShrink.com)

## Bentley Harris Expando PT

The most widely used braided sleeve in the industry, PET expandable braided sleeving makes up over 80% of the worlds consumption of expandable sleeving. Bentley Harris Expando PT is a highly abrasion resistant braided sleeve that is perfect for most applications.

### Features:

- Excellent cut through and abrasion resistance
- Continuous use temperature of -70°C to 125°C (-103°F to 257°F)
- Expando PT Plus contains a patented fray resistant treatment.
- Melt temperature of 230°C (446°F)
- Expands up to three times its resting diameter
- Halogen Free, ROHS compliant
- Self Extinguising
- Resists Gasoline, Engine Chemicals & Cleaning Solvents
- Braided from 10 mil polyethylene terephthalate (PET) monofilament yarns.
- Available in Black. Other Colors available

### Dimensions

Part Number	Diameter	Feet	Nominal Size	Expansion Min	Expansion Max
BSBHPT-0125	1/8"	2000 FT/SPOOL	1/8"	3/32"	1/4"
BSBHPT-025	1/4"	1000 FT/SPOOL	1/4"	1/8"	3/8"
BSBHPT-0375	3/8"	500 FT/SPOOL	3/8"	3/16"	5/8"
BSBHPT-050	1/2"	500 FT/SPOOL	1/2"	1/4"	3/4"
BSBHPT-075	3/4"	500 FT/SPOOL	3/4"	1/2"	1 1/4"
BSBHPT-125	1-1/4"	250 FT/SPOOL	1 1/4"	3/4"	1 3/4"
BSBHPT-175	1-3/4"	250 FT/SPOOL	1 3/4"	1"	2 3/4"
BSBHPT-200	2"	250 FT/SPOOL	2"	1 1/4"	3"
BSBHPT-250	2-1/2"	200 FT/SPOOL	2 1/2"	1 1/2"	4 1/2"