

A division of CSA Technical Solutions, LLC

1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010

www.BuyHeatShrink.com

Cold Shrink End Cap

Made of EPDM rubber Easy and fast installation Can meet a variety of configuration requirements Provide sealing protection over multi-core cable ends Used to seal cable during installation or storage, protecting cable ends against

Application

The Cold Shrink EC-Series End Caps protect cables, pipes and other cylindrical objects from exposure to moisture, contamination, corrosion, ozone, ultra-violet radiation, physical contact and other environmental hazards.

Features:

- Simple and fast installation, no tools required.
- Accommodating size ranges from 13mm 70mm.
- Sealing tight, high rebound even after prolonged years of aging and exposure.
- Water-resistant.
- No mastic or tape required.
- Resists fungus.
- Resists acids and alkalis.
- Resists ozone.
- Easily removed.
- No training required for installation.

Dimensions

Part Number	Diameter	Inches	Recovered ID (inches)	Recovered Thickness (inches)	Recovered Length (inches)	Application Range (inches)	Color
HSCC- 0787	20mm	0.787	0.394	0.098	3.937	0.512-0.591	Black
HSCC- 110	28mm	1.102	0.551	0.098	3.937	0.709-0.906	Black
HSCC- 185	47mm	1.85	0.827	0.106	3.937	0.984-1.496	Black
HSCC- 315	80mm	3.15	1.772	0.11	3.937	1.89-2.756	Black