



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Dual Monofilament PET Braided Cable Sleeving

General purpose dual monofilament PET braided sleeves. Our braided sleeving products are registered in the NASA database for low outgassing (under CS Technical as manufacturer); they are Halogen Free and ROHS compliant. These dual PET braided sleeves have a continuous use temperature of -70°C to 125°C (-103°F to 257°F) and a melt temperature of 260°C (500°F). They expand up to three times its resting diameter (3:1 Ratio) and their braided construction from 15 mil and 10 mil polyethylene terephthalate (PET) monofilament yarns makes them self extinguishing, highly resistant to gasoline, engine chemicals and most cleaning solvents.

Features:

- Excellent cut through and abrasion resistance
- Continuous use temperature of -70°C to 125°C (-103°F to 257°F)
- Melt temperature of 260°C (500°F)
- Expands up to three times its resting diameter
- Halogen Free, ROHS compliant
- Self Extinguishing
- Resists Gasoline, Engine Chemicals & Cleaning Solvents
- Braided from 15 mil and 10 mil polyethylene terephthalate (PET) monofilament yarns.
- Registered in the NASA database for low outgassing (under CS Technical as manufacturer)

Dimensions

Part Number	Diameter	Feet
BSDM025	1/4"	1000 FT/SPOOL
BSDM0375	3/8"	500 FT/SPOOL
BSDM050	1/2"	500 FT/SPOOL
BSDM075	3/4"	250 FT/SPOOL
BSDM100	1"	250 FT/SPOOL
BSDM125	1-1/4"	250 FT/SPOOL
BSDM150	1-1/2"	250 FT/SPOOL
BSDM175	1-3/4"	250 FT/SPOOL