

A division of CSA Technical Solutions, LLC 1959 Hammondville Road, Pompano Beach, FL 33069 Phone 954-978-0056 Fax 888-617-2010

www.BuyHeatShrink.com

Flat Braided Nomex Lacing Tape

Use a roll of Flat Braided Lacing Tape to manage any size cable bundle, from a couple of 22AWG wires to a fistful of heavy power cables. Instead of using Cable Ties, which leave a sharp edge that snags and turns brittle, degrading over time, Flat Braided Lacing Tape ensures a clean work profile. Certain industries, such as aerospace and aviation, specify laced harnesses as a design requirement for this reason. Lacing tape is ideal for lashing wires or cables to ladder bars, conduit, and other wire management solutions. Lacing tape also holds tight in a variety of professional knots with superior durability, water resistance, versatility, and abrasion resistance. It is suitable for securing wires, camping, gardening, marine applications and more.

Features:

- Nomex Lacing Tape is braided with high-temperature Nomex® aramid fibers
- Approximate operating Temperature range: -67°F to 500°F (-55°C to 260°C)
- MORE YARDS PER ROLL lasts longer
- MADE IN THE USA using the highest-quality Nomex
- Available Colors: Black lacing cord, or Natural lacing cord
- Length: 750ft 1500ft (250yd 500yd)
- Finish: No Finish and Synthetic Rubber

Dimensions

Part Number	Size	Min Break Strength (lbs)	Width		Thickness		Speel Size
			Min (in)	Max (in)	Min (in)	Max (in)	Spool Size (yds)
LC-NX-1	1	85	0.180	0.220	0.013	0.019	250 yd.
LC-NX-2	2	50	0.099	0.121	0.011	0.017	250 yd.
LC-NX-3	3	35	0.068	0.083	0.009	0.015	500 yd.
LC-NX-4	4	25	0.050	0.061	0.007	0.013	500 yd.