



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Flat Braided Nylon Lacing Tape

Use Nylon Lacing Tape for bundling and tying electrical wires, especially where flexibility is required. Try a basic lock-stitch or running-stitch, to organize and secure wire bundles for long-term stability. Lacing tape gives users the flexibility to break out branches of wiring along the harness and to design variable solutions for electrical wiring.

Our Nylon Lacing Tape (A-A-52080) is a general purpose lacing tape that is braid-manufactured from a high-tenacity continuous filament nylon yarn. Finished with a microcrystalline fungicide wax for longlasting durability & shelf life.

Features:

- Standard Colors: White or Black
- Temperature Range: -67°F to 250°F (-55°C to 121 °C)
- Finish: Microcrystalline Fungicide Wax, No Finish or Synthetic Rubber
- Nylon offers excellent knot tying properties
- High-temperature range performance
- Designed for and trusted by aerospace & NASA engineers
- Industry-Best Shelf Life for Lacing Tape

Dimensions

Part Number	Size	Yards	Min. Break Strength (lbs)	Width min (in)	Width max (in)	Thickness min (in)	Thickness max (in)
LC-NY-1	1	250	135	0.180	0.220	0.013	0.019
LC-NY-2	2	250	80	0.099	0.121	0.012	0.018
LC-NY-3	3	500	50	0.077	0.094	0.011	0.017
LC-NY-4	4	500	25	0.054	0.066	0.009	0.015
LC-NY-5	5	500	15	0.045	0.055	0.006	0.014