



A division of CSA Technical Solutions, LLC  
1959 Hammondville Road, Pompano Beach, FL 33069  
Phone 954-978-0056 Fax 888-617-2010  
[www.BuyHeatShrink.com](http://www.BuyHeatShrink.com)

## Flat Braided Teflon Lacing Tape

Use a roll of Flat Braided Lacing Tape to manage any size cable bundle, from a couple of 22AWG wires to a fistful of heavy power cables. Instead of using Cable Ties, which leave a sharp edge that snags and turns brittle, degrading over time, Flat Braided Lacing Tape ensures a clean work profile; certain industries, such as aerospace and aviation, specify laced harnesses as a design requirement for this reason. Lacing tape is ideal for lashing wires or cables to ladder bars, conduit, and other wire management solutions. Lacing tape also holds tight in a variety of professional knots with superior durability, water resistance, versatility, and abrasion resistance. It is suitable for securing wires, camping, gardening, marine applications and more.

### Features:

- Teflon Fiberglass Lacing Tape is braided with high tenacity, continuous filament glass yarn and coated with Teflon before braiding—Stays flat while in use
- Glass maintains strength and is stable to 800°F (427°C)
- MORE YARDS PER ROLL — Lasts Longer
- MADE IN THE USA
- Available Colors: Brown
- Teflon Finish

### Dimensions

Part Number	Size	Finish	Yards	Min Break Strength (lbs)	Width		Thickness	
					Min (in)	Max (in)	Min (in)	Max (in)
LC-TFE-2	2	No Finish	250	100	0.099	0.121	0.013	0.019
LC-TFE-4	4	No Finish	500	50	0.054	0.066	0.013	0.019
LC-TFE-5	5	No Finish	500	40	0.045	0.055	0.013	0.019