



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Medium Wall UNLINED Lined Heat Shrink Tubing

Medium Wall Unlined Heat Shrink is a tubing used for managing, protecting, and insulating cables and wires. This particular product is UV resistant, moisture proof, and lightweight for greater flexibility.

Features:

- Protects and insulates wires and cables.
- Medium wall provides flexibility.
- Abrasion and UV resistant.
- Complete moisture sealing.
- Simple shrink using heat gun.

Dimension

Part Number	Nominal	Expanded		Recovered			
		Internal Diameter (Min) D		Internal Diameter (Max) d		Wall Thickness (Nom) W	
		mm	in	mm	in	mm	in
HS3MW-0400	0.4"	10.2	0.40	3.8	0.15	2.0	0.080
HS3MW-0750	3/4"	19.1	0.75	5.6	0.22	2.0	0.080
HS3MW-1500	1-1/2"	38.1	1.50	12.7	0.50	2.4	0.095
HS3MW-1700	1.7"	43.2	1.70	12.7	0.50	2.5	0.100
HS3MW-2750	2-3/4"	69.9	2.75	25.4	1.00	2.5	0.100
HS3MW-3500	3-1/2"	88.9	3.50	30.0	1.18	2.5	0.100
HS3MW-4700	4.7"	119.4	4.70	39.9	1.57	2.7	0.105
HS3MW-6000	6"	152.4	6.00	50.8	2.00	3.0	0.120
HS3MW-9000	9"	228.6	9.00	77.0	3.00	3.3	0.130