



A division of CSA Technical Solutions, LLC  
**1959 Hammondville Road, Pompano Beach, FL 33069**  
**Phone 954-978-0056 Fax 888-617-2010**  
[www.BuyHeatShrink.com](http://www.BuyHeatShrink.com)

## Metal Barb Ties

Panduit cable ties are designed and manufactured to meet and exceed beyond industry standards for maximum reliability. These Panduit Pan-Ty cable ties are very adaptable and can be found useful in both indoor and outdoor environments. For an even larger maximum bundle diameter, these cable ties can be linked together to accommodate the largest diameters. These Panduit Pan-Ty cable ties are UL-94V-2 rated, RoHS compliant and are made from Nylon 6.6 material. There are limitless amount of applications these cable ties can be used for. The one piece construction gives high performance and reliability and the operating temperature with this cable ties is 185 degrees Fahrenheit. Buyheatsrink.com has a variety of Panduit Pan-Ty cable ties available for ordering. Some of the features available differ in nominal size, tensile loop strength, and color. The smallest of the nominal lengths is the 4” size, which has a maximum loop tensile of 18 pounds. This option is available in either black or natural color and comes in convenient bags of 1000. The 7” Pan-Tys have a 50 pound loop tensile, and also come in bags of 1000 in either black or natural. The 8” cable ties have a 40 pound loop tensile strength and come in quantities of 1000 in either black or natural. The 11” Pan-Tys have a 50 pound loop tensile strength and also come in bags of 1000 in either black or natural. The largest nominal size of the Panduit Pan-Ty cable ties is 14” which has a 50 pound loop tensile strength. This option is available in either black or natural bags of 1000. Don’t forget to check out our Cable Tie Tool (see right) to help with the cutting off of cable tie tails and adjusting tensioning with 18-50 pound loop tensile strength cable tie.

### Features:

- Featuring a curved tip, these ties are easy to pick up from flat surfaces and initial threading is faster RoHS
- Compliant Material: Nylon 6.6 (Black is weather resistant and UV Stabilized)
- Material Flammability Rating UL94V-2

### Dimensions

Part Number	Panduit Part Number	Length	Bag	Nominal Size	Loop Tensile	Max Bundle Diameter
CT-BT1M	BT1M-M	4"	1000 PCS/BAG	4"	18 LB	0.9"
CT-BT2S	BT2S-M	7"	1000 PCS/BAG	7"	50 LB	1.9"
CT-BT2M	BT2M-M	8"	1000 PCS/BAG	8"	18 LB	2.2"
CT-BT3S	BT3S-M	11"	1000 PCS/BAG	11"	50LB	3.0"