



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Nu-Tech Heat Shrink Wrap Sleeve Kit

A wrap-around heat-shrinkable cable jacket can be easily applied in the field without having to split the cable line. Wrap is a simple alternative for effective insulation repairs.

- Designed to repair and seal damaged wire jackets that have been chafed, have radial cracks, or cuts on the insulation anywhere cable jacketing has become compromised.
- Used as a side entry repair kit.
- Nu-Tech's wrap kit consists of an outer tubing provided with a hot melt adhesive inner layer and supplied with welding adhesive in a low profile construction that provides easy access for repairing damaged wires.

Features:

- Excellent cut through and abrasion resistance
- High quality superior Crosslinked Polyolefin
- Continuous use temperature of -55°C to 135°C
- Flame Retardant (Rated Non-Burning)
- shrinks down as much as 10 times its as supplied diameter (Up to 10:1 Ratio)
- NAFTA, ROHS & ELV compliant
- UV resistant color Carbon Black
- Resists Gasoline, Engine Chemicals & Cleaning Solvents
- -55C Low Temperature Flexibility (ASTM D-2671 C)
- Registered in the NASA database Cage Code 1UGZ7

Dimensions

Part Number	NuTech PN	Width	Supplied Length	Max Suggested Diameter	Type	Wall thickness as supplied	Wall thickness after shrinking	Length after shrinking
HSW-2.3-3	NUWS.75	2.3"	3"	0.5	Smooth	0.08"	0.16"	1"
HSW-3-2.3	NUWS-80X025	3"	2.3"	0.375	Smooth	0.04"	0.13"	2.0"
HSW-4.3-4	NUWS-137X050	4.3"	4"	1	Smooth	0.04"	0.13"	3.5"
HSW-5-12	NUWS-380X150	5"	12"	3	Smooth	0.05"	0.17"	4.0"
HSW-6.5-3.75	NUWS-200X075	6.5"	3.75"	0.75	Smooth	0.05"	0.15"	5.5"
HSW-9-11	NUWS-3.00	9"	11"	2.5	Ribbed	0.05"	0.16"	7.0"
HSW-10.5-19	NUWS-6.00	10.5"	19"	4.5	Ribbed	0.08"	0.19"	8.5"
HSW-10.75-6.5	NUWS-2.00	10.75"	6.5"	1.4	Ribbed	0.05"	0.16"	9.5"
HSW-11-6	NUWS-1.50	11"	6"	1.3	Ribbed	0.05"	0.16"	10"