



A division of CSA Technical Solutions, LLC  
1959 Hammondville Road, Pompano Beach, FL 33069  
Phone 954-978-0056 Fax 888-617-2010  
[www.BuyHeatShrink.com](http://www.BuyHeatShrink.com)

## Nu-Tech High Ratio Heat Shrink Tubing

HIGH RATIO Heat-Shrink Tubing

Heavy-Wall Crosslinked Polyolefin

Waterproof Seal! Hot melt adhesive lining flows with heat to fill voids and crevices upon recovery.

### Features:

- Excellent cut through and abrasion resistance
- High quality superior Crosslinked Polyolefin
- Continuous use temperature of -55°C to 135°C
- Flame Retardant (Rated Non-Burning)
- Expands up to ten times its resting diameter (Up to 10:1 Ratio)
- NAFTA, ROHS & ELV compliant
- UV resistant color Carbon Black w/ Yellow Printing
- Resists Gasoline, Engine Chemicals & Cleaning Solvents
- -55C Low Temperature Flexibility (ASTM D-2671 C)
- Registered in the NASA database Cage Code 1UGZ7

### Dimensions

Manufacturer Part PN	Diameter	Tyco PN	NuTech PN	ID Before Shrink	ID after shrinking	Min wall recovered
HSHRT-075	3/4"	91385-1	NUHRT-.75	0.75	0.12	0.175"
HSHRT-150	1-1/2"	91385-2	NUHRT-1.5	1.5	0.23	0.166"
HSHRT-200	2"	91385-3	NUHRT-2	2	0.34	0.176"
HSHRT-300	3"	91385-4	NUHRT-3	3	0.5	0.181"
HSHRT-450	4.5"	91385-5	NUHRT-4.5	4.5	0.75	0.200"
HSHRT-600	6"	91385-6	NUHRT-6.0	6	1.5	0.200"