



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Nylon Monofilament Braided Cable Sleeving

Our nylon mono expandable braided sleeve is commonly used in the automotive industry due to its resistance to gasoline, engine chemicals, automotive fluids, and cleaning solvents. It has excellent cut through and abrasion resistance, expands up to three times its resting diameter (3:1); It is self extinguishing, UV resistant, Halogen Free and ROHS compliant. Our mono nylon sleeving is braided from 12 mil Nylon 6,6 monofilament yarns. It has a continuous use temperature of -45°C to 150°C (-49°F to 302°F) and a melt temperature of 256°C (493°F)

Features:

- Excellent cut through and abrasion resistance
- Continuous use temperature of -45°C to 150°C (-49°F to 302°F)
- Melt temperature of 256°C (493°F)
- Expands up to three times its resting diameter
- Halogen Free, ROHS compliant
- Self Extinguishing
- Resists Gasoline, engine chemicals, other automotive fluids, and cleaning solvents
- Braided from 12 mil Nylon 6,6 monofilament yarns.
- UV resistant

Dimensions

Part Number	Diameter	Feet	Expansion Min	Expansion Max
BSNY0125	1/8"	2000 FT/SPOOL	3/32"	1/4"
BSNY025	1/4"	1000 FT/SPOOL	1/8"	3/8"
BSNY050	1/2"	500 FT/SPOOL	1/4"	3/4"
BSNY075	3/4"	250 FT/SPOOL	1/2"	3/4"
BSNY100	1"	250 FT/SPOOL	5/8"	1 3/8"
BSNY125	1-1/4"	250 FT/SPOOL	3/4"	1-1/4"