



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Nylon Multifilament Braided Cable Sleeving

Our nylon multifilament cable braided sleeve has a soft fabric feel yet it is highly resistant to abrasion, cuts, UV damage, vibration and common automotive & marine chemicals such as gasoline, engine chemicals and cleaning solvents. Nylon multi braided sleeving will not retain moisture and resists microbial (mildew) growth making it highly suitable for marine applications. This high quality protective sleeving is virtually non-expandable, halogen free and RoHS compliant. With continuous use temperature of -45C to 150C (-49F to 302F) and melt temperature of 256C (493F), it expands up to three times its resting diameter.

Features:

- Excellent cut through and abrasion resistance
- Soft fabric like feel
- Continuous use temperature of -70C to 125C (-103F to 257F)
- Melt temperature of 250C (482F)
- Virtually non-expandable
- Available in a very wide variety of sizes to suit your needs
- Halogen Free, ROHS compliant
- Resists Gasoline, Engine Chemicals & Cleaning Solvents
- Will not retain moisture, and resists microbial (mildew) growth - highly suitable for Marine applications.

Dimensions

Part Number	Diameter	Feet
BSNYMF0125	1/8"	1000 FT/SPOOL
BSNYMF0188	3/16"	1000 FT/SPOOL
BSNYMF025	1/4"	500 FT/SPOOL
BSNYMF0313	5/16"	500 FT/SPOOL
BSNYMF0375	3/8"	250 FT/SPOOL
BSNYMF050	1/2"	250 FT/SPOOL
BSNYMF0625	5/8"	250 FT/SPOOL
BSNYMF075	3/4"	250 FT/SPOOL
BSNYMF0875	7/8"	250 FT/SPOOL
BSNYMF100	1"	200 FT/SPOOL
BSNYMF125	1-1/4"	125 FT/SPOOL
BSNYMF150	1-1/2"	100 FT/SPOOL
BSNYMF200	2"	100 FT/SPOOL
BSNYMF250	2-1/2"	100 FT/SPOOL

BSNYMF300	3"	100 FT/SPOOL
BSNYMF400	4"	100 FT/SPOOL