



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Nylon Spiral Wrap

Made from Nylon 6, spiral wrap is a self extinguishing material that does not emit any toxic or irritating byproducts. It is well suited for use under high temperatures and brief exposure to open flame. It can be used in enclosed environments (unlike Polyethylene), and is lightweight and highly abrasion resistant. Our Nylon spiral wrap is available in Natural, and weather resistant Black (for use outdoors).

Features:

- Continuous operating temperature -40°F to 250°F (-40°C to 121°C)
- Abrasion resistance - very good (superior to polyethylene)
- Specific gravity (ASTM D792-66) = 1.14 (sinks in water)
- Highly solvent resistant
- Degrades in strong Acids
- Highly Alkaline resistant
- 1.5% moisture absorption
- Self Extinguishing
- MIL M-20693B Type I, MIL M-22096A LP 410A, MIL M-19098 approved

Dimensions

Part Number	Diameter	Roll	OD Size	Wall Thickness	Suggested bundle size
SW-NY-0125	1/8"	100 FEET/ROLL	1/8"	0.032"	1/4"
SW-NY-0188	3/16"	100 FEET/ROLL	3/16"	0.032"	3/8"
SW-NY-025	1/4"	100 FEET/ROLL	1/4"	0.035"	1/2"
SW-NY-0375	3/8"	100 FEET/ROLL	3/8"	0.052"	3/4"
SW-NY-050	1/2"	100 FEET/ROLL	1/2"	0.052"	1"
SW-NY-075	3/4"	100 FEET/ROLL	3/4"	0.062"	2"
SW-NY-100	1"	100 FEET/ROLL	1"	0.065"	3"