



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

2:1 Flexible Fluoropolymer Heat Shrink tubing

Use Fluoropolymer PTFE for applications of extreme electrical, thermal, and chemical environments—ideal for use in strain relief and as fiber optic splice cover. Excellent dielectric insulating properties, extremely lubricious, chemically resistant and inert. The chemical inertness of PTFE heat shrink tubing combined with its high-temperature resistance make it an unparalleled electrical insulator.

Part Number	MilSpecification - MPN	Diameter	Feet
HSKF-0047	AMS-DTL-23053/18-201-C	3/64"	500 FT/SPOOL
HSKF-0063	AMS-DTL-23053/18-202-C	1/16"	500 FT/SPOOL
HSKF-0094	AMS-DTL-23053/18-203-C	3/32"	500 FT/SPOOL
HSKF-0125	AMS-DTL-23053/18-204-C	1/8"	500 FT/SPOOL
HSKF-0188	AMS-DTL-23053/18-205-C	3/16"	250 FT/SPOOL
HSKF-025	AMS-DTL-23053/18-206-C	1/4"	250 FT/SPOOL
HSKF-0375	AMS-DTL-23053/18-207-C	3/8"	200 FT/SPOOL
HSKF-050	AMS-DTL-23053/18-208-C	1/2"	200 FT/SPOOL
HSKF-075	AMS-DTL-23053/18-209-C	3/4"	100 FT/SPOOL
HSKF-100	AMS-DTL-23053/18-210-C	1"	100 FT/SPOOL