



A division of CSA Technical Solutions, LLC
1980 NW 44th St Deerfield Beach, FL 33064
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

2:1 Flexible Fluoropolymer Heat Shrink tubing

Use Fluoropolymer PTFE for applications of extreme electrical, thermal, and chemical environments—ideal for use in strain relief and as fiber optic splice cover. Excellent dielectric insulating properties, extremely lubricious, chemically resistant and inert. The chemical inertness of PTFE heat shrink tubing combined with its high-temperature resistance make it an unparalleled electrical insulator.

Dimensions

Part Number	Diameter	Mil Spec - MPN
HSKF-0047	3/16"	AMS-DTL-23053/18-201-C
HSKF-0063	1/16"	AMS-DTL-23053/18-202-C
HSKF-0094	3/32"	AMS-DTL-23053/18-203-C
HSKF-0125	1/8"	AMS-DTL-23053/18-204-C
HSKF-0188	3/16"	AMS-DTL-23053/18-205-C
HSKF-025	1/4"	AMS-DTL-23053/18-206-C
HSKF-0375	3/8"	AMS-DTL-23053/18-207-C
HSKF-050	1/2"	AMS-DTL-23053/18-208-C
HSKF-075	3/4"	AMS-DTL-23053/18-209-C
HSKF-100	1"	AMS-DTL-23053/18-210-C