



A division of CSA Technical Solutions, LLC
1980 NW 44th St Deerfield Beach, FL 33064
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

3 to 1 Polyolefin Heat Shrink Tubing

- 3:1 Shrink Ratio (shrinks to 1/3 its original diameter)
- Meets requirements of AMS-DTL-23053/5 (formerly MIL-I-23053/5), Classes 1, 2 (Clear), and 3
- UL 224 **VW-1** and CSA OFT recognized
- Maximum Continuous use temperature 135C
- Shrink Temperature of 100°C and operating temperature of -55°C to + 135°C
- Crosses to: Sumitomo B2(3X), Raychem RNF-3000, Alpha FIT-321V, Canusa CPX-300, LG GSHS-3635

Specifications/Approvals:

Military: AMS-DTL 23053/5 (Formerly Mil-I-23053/5)

Underwriters Lab: UL 224 600V, 125°C, **VW-1**

CSA C22.2

Crosses to: Sumitomo B2(3X), Raychem RNF-3000, Alpha FIT-321V, Canusa CPX-300, LG GSHS-3635

Dimension

Internal PN	Expanded			Recovered			
	Nominal Size	Inside Diameter		Inside Diameter		Minimum Wall Thickness	
		in	mm	in	mm	in	mm
HS3-0063	1/16"	0.060	1.5	0.019	0.5	0.018	0.45
HS3-0125	1/8"	0.118	3.0	0.039	1.0	0.022	0.55
HS3-0188	3/16"	0.177	4.5	0.059	1.5	0.022	0.60
HS3-025	1/4"	0.236	6.0	0.079	2.0	0.026	0.65
HS3-0375	3/8"	0.354	9.0	0.118	3.0	0.030	0.75
HS3-050	1/2"	0.472	12.0	0.157	4.0	0.030	0.75
HS3-075	3/4"	0.709	12.0	0.236	6.0	0.033	0.85
HS3-100	1"	0.944	24.0	0.315	8.0	0.039	1.00
HS3-150	1-1/2"	1.534	39.0	0.512	13.0	0.045	1.15