



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

3:1 Printable Heat Shrink Tubing PreFlattened

Use Printable Heat Shrink Tubing for readily identifiable cable marking and professionalism at the job site. Pre-Flattened heat shrink allows for efficient printing with commercially available [Heat Shrink Printers](#), while also accommodating the “modified label printers,” more commonly used for creating pre-printed heat shrink. Pre-Flattened heat shrink features the same properties as our standard 3:1 heat shrink tubing and is specially designed and spooled for use on thermal transfer label printers. Available in Yellow and White, and a variety of sizes, our pre-flattened printable 3:1 shrink ratio shrink tubing works with the Kroy K4350 printer or any I-Class printers, guaranteed to be your long-lasting labeling solution.

Features:

- 3:1 Shrink Ratio (shrinks to 1/3 its original diameter)
- Meets requirements of AMS-DTL-23053/5 (formerly MIL-I-23053/5), Classes 1, 3
- UL 224 VW-1 and CSA OFT recognized
- Maximum Continuous use temperature 135C
- Shrink Temperature of 100°C and operating temperature of -55°C to + 135°C
- Typical applications include: Insulation, Wire Identification, Wire Bundling, Mechanical Protection, Color Coding, Lightweight Harnessing, Physical/Electrical Protection of Components, Strain Relief, and Solder Insulation.

Dimensions

Part Number	Diameter	Nominal ID	ID After Shrink	Flat Width
HS3F-0094	3/32"	3/32"	0.031"	1/8"
HS3F-0125	1/8"	1/8"	0.039"	3/16"
HS3F-0188	3/16"	3/16"	0.059"	5/16"
HS3F-025	1/4"	1/4"	0.078"	3/8"
HS3F-0375	3/8"	3/8"	0.125"	9/16"
HS3F-050	1/2"	1/2"	0.167"	13/16"
HS3F-075	3/4"	3/4"	0.25"	1-3/16"
HS3F-100	1"	1"	0.375"	1-9/16"
HS3F-150	1-1/2"	1-1/2"	0.5"	2-3/8"