



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

[AMTI Slice 141 Heat Shrink Tubing Cutter](#)

The Model 141 shrink tubing cutter will cut up to 5200 4 inch piece in 1 hour! With an adjustable input space of 1.5" x 3", you can cut a wide range of wire and tubing in sizes up to 1 gauge, and hollow tubing up to 1.5" OD. Feed rates range from 1" per second up to 30" per second. Machine comes equipped with adjustable guides and chute opening for clean, square cuts. Standard cut accuracy +/- 1 mm. Cuts adhesive-lined heat shrink tubing, basic polyolefin heat shrink, convoluted loom tubing (split or unsplit), and many other types. Tubing sold separately. Please contact us if the option you want is not shown on the website

Safety Features

- Two-handed operation requires operator to simultaneously press each button, located (1) one each side of machine to activate operation.
- Large red "emergency stop" switch located at top of unit, that stops cutting wire or tubing when pressed.
- Plexiglas safety shield, held magnetically in place covers the keyboard to prevent unintended activation.

Power & Air Requirements: 115/230 volts at 50/60-hertz single phase and air pressure maintained @ 80 psi min

System Size: Overall Height 19" x Housing Height 13"

Unit Weight: 55 LBS

Warranty:

Every model carries the same one year warranty on electronics and mechanical elements (exclusive of blades or poly-wheels) or one million cuts, whichever comes first.

Features:

- Adjustable chute opening to accommodate many different types of tubing up to and including 1.5" OD
- Precision Engineered and machined with State of the Art CNC (Computer Numerical Control) Machining.
- Aluminum, stainless steel and hardened tool steel construction
- Simple changeover procedure allows you to switch products and/or speeds in seconds.
- Adjustable cutting speed from 1"-30 inches per second
- Easy to load product utilizing adjustable, triple-roller guide wheels.
- Spring Loaded drive tension with one drive wheel and one idler wheel to enhance pulling action.
- Polyurethane coated wheels so your tubing doesn't get scratched..
- User friendly touch controls with numeric keypad and easy to read LCD readout
- Up to 99 stored standard programs with up to 30 additional "batch programs". each "batch" program can contain up to 10 standard programs.
- User selected units of either inches or millimeters
- Accuracy is within +/- 1.0 millimeter
- All air filters and regulators are included

Part Number	Optional Components
CUT-141	Slice 141 Cutter
CUT-141-BLADE	Replacement blade for Slice 141 Cutter
CUT-141-DIE	Die Bottom for Slice 141 Cutter