



A division of CSA Technical Solutions, LLC
1980 NW 44th St Deerfield Beach, FL 33064
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Adhesive Lined Heat Shrink Tubing 2:1

Our 2:1 heat shrink tubing is also available with a "dual-wall" construction. When exposed to heat (usually a bit lower than the activation temperature of the heat shrink), the inner layer begins to flow (just like a hot melt glue). When the tubing shrinks and cools down, inner layer forms an adhesion layer between the tubing and the component or wire. This provides a water-tight seal, protecting the connector and/or wire.

Features:

- Good mechanical strength and cut-through resistance
- Environmentally seals and protects
- Meets UL, CSA and military specifications
- RoHS compliant
- Operating temperature range -40°C to 130°C
- Sizes range from 1/8" to 2"
- Standard color is black
- AMS-DTL-23053/4 Class 1, 2 & 3.
- UL/CSA

Dimension

Part Number	Diameter	Mil Specification	Length
HS2A-0125	1/8"	N/A	4ft
HS2A-0188	3/16"	N/A	4ft
HS2A-025	1/4"	AMS-DTL-23053/4-201-0	4ft
HS2A-0375	3/8"	AMS-DTL-23053/4-202-0	4ft
HS2A-050	1/2"	AMS-DTL-23053/4-203-0	4ft
HS2A-075	3/4"	AMS-DTL-23053/4-204-0	4ft
HS2A-100	1"	AMS-DTL-23053/4-205-0	4ft
HS2A-150	1-1/2"	AMS-DTL-23053/4-206-0	4ft