



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Ben Har 1151-XL-240 (Extruded Silicone) Fiberglass Sleeving

Silicone coated fiberglass braided sleeving is commonly used in high voltage applications such as motors, transformers, welding apparatus, coils, and lighting ballasts. Because of its versatility and 240°C temperature rating, acrylic coated fiberglass sleeving has also found many uses in appliances such as lighting fixtures (ballasts), stoves, oven and furnace controls, relays, breaker panels, and many other commercial and industrial applications.

Features:

- Tightly braided fiberglass sleeve completely coated with acrylic resin to provide superior electrical and thermal protection.
- Thermal Characteristics - UL/NEMA Thermal Class R (-25 to 240°C)
- Meets Mil-I-3190/9
- CSA rated
- Available in NEMA sizes #24 (AWG) to 2". NEMA TF-1, Type 5
- Designed to perform for long periods in a 240°C range without loss of any electrical or physical properties.
- Dielectric Grade A: 7000V minimum average breakdown, 5000V minimum individual.
- High quality equivalent to: Ben-Har XL-240, Varglas Silicone Resin Class H-A-1
- Iron Oxide Red Color

Dimensions

Part Number	Manufacturer Part Number	Size	Feet	ID
BSBH-XL240-024	BSBH-XL240-024	24 AWG	500 FT/SPOOL	0.022
BSBH-XL240-022	BSBH-XL240-022	22 AWG	500 FT/SPOOL	0.027
BSBH-XL240-020	BSBH-XL240-020	20 AWG	500 FT/SPOOL	0.034
BSBH-XL240-018	BSBH-XL240-018	18 AWG	500 FT/SPOOL	0.042
BSBH-XL240-016	BSBH-XL240-016	16 AWG	500 FT/SPOOL	0.053
BSBH-XL240-010	BSBH-XL240-010	10 AWG	250 FT/SPOOL	0.106
BSBH-XL240-009	BSBH-XL240-009	9 AWG	250 FT/SPOOL	0.118
BSBH-XL240-007	BSBH-XL240-007	7 AWG	250 FT/SPOOL	0.148

BSBH-XL240-005	BSBH-XL240-005	5 AWG	125 FT/SPOOL	0.186
BSBH-XL240-003	BSBH-XL240-003	3 AWG	125 FT/SPOOL	0.234
BSBH-XL240-002	BSBH-XL240-002	2 AWG	125 FT/SPOOL	0.263
BSBH-XL240-00	BSBH-XL240-00	0 AWG	50 FT/SPOOL	0.33
BSBH-XL240-7-16	BSBH-XL240-7-16	7/16"	50 FT/SPOOL	0.45
BSBH-XL240-3-4	BSBH-XL240-3-4	3/4"	50 FT/SPOOL	0.786
BSBH-XL240-7-8	BSBH-XL240-7-8	7/8"	50 FT/SPOOL	0.893
BSBH-XL240-1	BSBH-XL240-1	1"	50 FT/SPOOL	1.018