



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Bentley Harris Roundit 2000

Bentley Harris Roundit 2000 is a unique side entry product manufactured from a blend of monofilaments and multifilaments, giving the product the strength and abrasion resistance of comparable plastic products

(like split wire loom), and the look of a fabric or cloth tape. It is easy to assemble because of the longitudinal (lengthwise) split, and the soft aesthetically pleasing look of a fabric.

Made from Polyethylene Terephthalate (PET), our PET wrap braided sleeving is suitable for use in automotive and marine applications with a continuous use temperature of 125°C. It doesn't trap moisture, and the material itself is highly resistance to mold and rot generation.

The self-wrapping feature of Roundit 2000 products allows for quick and easy installation and removal of the product for assembly and maintenance. Roundit 2000 may be applied or removed without any manipulation of connectors or fittings and offers an innovative solution in areas where breakouts are necessary. Its wrappable construction allows stocking of a limited range of sizes to cover a wide range of diameters. Roundit 2000 has many applications in the marine, railway, electronics, furniture accessory, and general manufacturing industries.

Features:

- Excellent cut through and abrasion resistance
- Continuous use temperature of -70°C to 125°C (-103°F to 257°F)
- Self wrapping design for use on already in place wiring systems. • Melt temperature of 230°C (446°F) • Easy to apply and remove.
- Halogen Free, ROHS compliant
- Self Extinguishing - please click here to see the definition of LOI, and how it relates to the burning of materials
- Resists Gasoline, Engine Chemicals & Cleaning Solvents
- Available in Black. Other Colors available

Dimensions

Part Number	Diameter	Feet	Nominal Size	Expansion min	Expansion Max
BSBHRI-0188	3/16"	492 FT/SPOOL	3/16"	1/8"	5/16"
BSBHRI-0313	5/16"	328 FT/SPOOL	5/16"	3/16"	3/8"
BSBHRI-050	1/2"	164 FT/SPOOL	1/2"	1/4"	5/8"
BSBHRI-075	3/4"	82 FT/SPOOL	3/4"	1/2"	1"
BSBHRI-100	1"	82 FT/SPOOL	1"	3/4"	1-1/4"
BSBHRI-125	1-1/4"	49 FT/SPOOL	1 1/4"	1"	1-1/2"

BSBHRI-150	1-1/2"	49 FT/SPOOL	1 1/2"	1-1/4"	1-3/4"
------------	--------	-------------	--------	--------	--------