



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Economical 2:1 Polyolefin Heat Shrink Tubing Spool

Features:

- 2:1 Shrink Ratio (shrinks to ½ its original diameter)
- Meets requirements of SAE AMS-DTL-23053/5 (formerly MIL-I-23053/5, MIL-DTL-23053/5), Classes 1, 2 (Clear), and 3
- UL 224 VW-1 and CSA OFT recognized
- Maximum Continuous use temperature 135°C
- 12 standard colors: Black, Clear, Red, White, Blue, Yellow, Brown, Gray, Orange, Green, Violet and Yellow/Green
- Shrink Temperature of 120°C and operating temperature of -55°C to + 135°C
- Crosses to : Sumitomo B2, Raychem RNF-100, Alpha FIT-221, 3M FP301 heat shrink, Canusa CPX-100, LG GSHS-1635F
- Typical applications include: Insulation, Wire Identification, Wire Bundling, Mechanical Protection, Color Coding, Lightweight Harnessing, Physical/Electrical Protection of Components, Strain Relief, and Solder Insulation.
- RoHS compliant

NOTE: This is the same quality heat shrink that we sell in bulk, just offered in smaller quantities.

For Larger Quantities or Sizes Not Shown here, check out the 2:1 Polyolefin Heat Shrink Page.

Dimensions

Part Number	Diameter	Feet	Mil Specification #	ID Before Shrink	ID After Shrink	Wall After Shrink	Flat Width
HS2-0047	3/64"	50 FT/SPOOL	AMS-DTL-23053/5-101	0.046"	0.023"	0.018"	1/16"
HS2-0063	1/16"	50 FT/SPOOL	AMS-DTL-23053/5-102	0.063"	0.031"	0.018"	1/8"
HS2-0094	3/32"	50 FT/SPOOL	AMS-DTL-23053/5-103	0.093"	0.046"	0.019"	1/8"
HS2-0125	1/8"	50 FT/SPOOL	AMS-DTL-23053/5-104	0.125"	0.062"	0.019"	3/16"
HS2-0188	3/16"	25 FT/SPOOL	AMS-DTL-23053/5-105	0.187"	0.093"	0.019"	5/16"
HS2-025	1/4"	25 FT/SPOOL	AMS-DTL-23053/5-106	0.25"	0.125"	0.026"	3/8"
HS2-0375	3/8"	25 FT/SPOOL	AMS-DTL-23053/5-107	0.375"	0.187"	0.026"	9/16"
HS2-050	1/2"	25 FT/SPOOL	AMS-DTL-23053/5-108	0.5"	0.25"	0.029"	13/16"
HS2-0625	5/8"	25 FT/SPOOL	AMS-DTL-23053/5-5/8	0.625"	0.313"	0.033"	1"
HS2-075	3/4"	15 FT/SPOOL	AMS-DTL-23053/5-109	0.75"	0.37"	0.035"	1-3/16"

HS2-100	1"	10 FT/SPOOL	AMS-DTL- 23053/5-110	1"	0.5"	0.039"	1-9/16"
HS2-125	1-1/4"	10 FT/SPOOL	N/A	1.26"	0.63"	0.039"	1-15/16"