



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Flat Braided Polyester Lacing Tape

Use a roll of Flat Braided Lacing Tape to manage any size cable bundle, from a couple of 22AWG wires to a fistful of heavy power cables. Instead of using Cable Ties, which leave a sharp edge that snags and turns brittle, degrading over time, Flat Braided Lacing Tape ensures a clean work profile; certain industries, such as aerospace and aviation, specify laced harnesses as a design requirement for this reason. Lacing tape is ideal for lashing wires or cables to ladder bars, conduit, and other wire management solutions. Lacing tape also holds tight in a variety of professional knots with superior durability, water resistance, versatility, and abrasion resistance. It is suitable for securing wires, camping, gardening, marine applications and more.

Features:

- Polyester Lacing Tape is braided with high tenacity, continuous filament polyester yarn.
- Approximate Operating Temperature range: 100°F to 350°F (-73°C to 177°C)
- MORE YARDS PER ROLL — Lasts Longer
- MADE IN THE USA using the highest-quality polyester and wax coating
- Available Colors: Black and Natural
- Available Length: 750ft - 1500ft (250yd - 500yd)
- Available Finish: No Finish, Waxed or Synthetic Rubber
- See table below for finishes available.
- Other colors available upon request.

Dimensions

Part Number	Mil-Spec Size	Min. Break Strength	With		Thickness		Spool size
			(min)	(max)	(min)	(max)	
LC-P-1	1	135	0.180	0.220	0.013	0.019	250 yd.
LC-P-2	2	80	0.099	0.121	0.012	0.018	250 yd.
LC-P-3	3	50	0.077	0.094	0.011	0.017	500 yd.
LC-P-4	4	25	0.054	0.066	0.009	0.005	500 yd.
LC-P-5	5	15	0.045	0.055	0.006	0.014	500 yd.