



A division of CSA Technical Solutions, LLC
1980 NW 44th St Deerfield Beach, FL 33064
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

[Heat Shrink Nyax Butt Connector](#)

Create quick and secure connections for wires with Heat Shrink Nyax Butt Connectors. Our Heat Shrink Nyax Butt Terminals are made to withstand harsh environments—these terminals feature a heat shrink connection that also has an internal sealant. After crimping the terminal onto the wire, simply apply heat to seal this wire crimp connector. Heat shrink insulation protects the life of your connection for a durable seal.

Features:

- 22-18 AWG (Red) /16-14 AWG (Blue) /12-10 AWG (Yellow)
- Shrink ratio 2:1
- Minimum recommended shrink temperature: 80°C / 176°F
- Minimum recommended solder melting temperature: 138°C / 280.4°F
- No wire damage due to low shrink temperature
- Best shrink temperatures: 125°C - 130°C / 257°F - 266°F

Dimensions

Part Number	MPN	Size	Terminal Type
HSCS-NY-L-22-18	40082L	22-18 AWG	Long
HSCS-NY-22-18	40082	22-18 AWG	Standard
HSCS-NY-16-14	40172	16-14 AWG	Standard
HSCS-NY-12-10	40312	12-10 AWG	Standard
HSCS-NY-L-12-10	40312L	12-10 AWG	Long