



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

PE Polyethylene Spiral Cable Wire Wrap Tube

Polyethylene is ideal for general applications. It is a low cost material that is highly abrasion resistant and is unaffected by most solvents. Our Polyethylene spiral wrap is available in many different colors, including: UV Resistant Black, Natural, Red, White, Blue, Green, Orange, Yellow, Brown, Gray, Neon Orange, Neon Pink, Neon Green, and Neon Yellow. All of our Neon colors are UV reactive (i.e. they fluoresce under UV light). If a specific color is not listed under the size you want, please feel free to call us for availability.

Features:

- Continuous operating temperature -76°F to 190°F (-60°C to 88°C)
- Abrasion resistance - good
- Specific gravity (ASTM D792-66) = 0.92 (floats in water)
- Highly solvent resistant up to 122°F (50°C)
- Highly acid resistant
- Highly Alkaline resistant
- Very little moisture absorption (0.014%)
- Mil-I-631D, Mil-P-21922A approved

Dimensions

Part Number	Diameter	Roll	Wall Thickness	Suggested Bundle Size
SW-0125	1/8"	100 FEET/ROLL	0.032"	1/4"
SW-0188	3/16"	100 FEET/ROLL	0.032"	3/8"
SW-025	1/4"	100 FEET/ROLL	0.035"	1/2"
SW-0375	3/8"	100 FEET/ROLL	0.052"	3/4"
SW-50	1/2"	100 FEET/ROLL	0.052"	1"
SW-0625	5/8"	100 FEET/ROLL	0.052"	1-1/2"
SW-075	3/4"	100 FEET/ROLL	0.062"	2"
SW-100	1"	75 FEET/ROLL	0.065"	3"