



A division of CSA Technical Solutions, LLC
1980 NW 44th St Deerfield Beach, FL 33064
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Semi-Rigid Polyolefin Heat Shrink Tubing

Features:

- Heat Shrink Tubing for wire splitting, bundling, and soldered connections
- Highly resistant to abrasion, chemical, and oil damage
- Flame retardant
- Shrinks to half size (2:1)
- Strong, semi-flexible material optimal for mechanical environments

Dimensions

Internal Part Number	Expanded				Recovered			
	Mil Spec #	Nominal	Inside Diameter		Inside Diameter		Minimum Wall Thickness	
	AMS-DTL-23053/5-	Size	in	mm	in	mm	in	mm
HS2SR-0047	AMS-DTL-23053/5-101 and 301	3/64"	0.046	1.2	0.023	0.58	0.018	0.45
HS2SR-0063	AMS-DTL-23053/5-102 and 302	1/16"	0.063	1.6	0.031	0.79	0.018	0.45
HS2SR-0094	AMS-DTL-23053/5-103 and 303	3/32"	0.093	2.4	0.046	1.17	0.019	0.50
HS2SR-0125	AMS-DTL-23053/5-104 and 304	1/8"	0.125	3.2	0.062	1.57	0.019	0.50
HS2SR-0188	AMS-DTL-23053/5-105 and 305	3/16"	0.187	4.8	0.093	2.36	0.019	0.50
HS2SR-025	AMS-DTL-23053/5-106 and 306	1/4"	0.250	6.4	0.125	3.18	0.026	0.65
HS2SR-0375	AMS-DTL-23053/5-107 and 307	3/8"	0.375	9.5	0.187	4.75	0.026	0.65
HS2SR-050	AMS-DTL-23053/5-108 and 308	1/2"	0.5	12.7	0.25	6.35	0.029	0.75
HS2SR-075	AMS-DTL-23053/5-109 and 309	3/4"	0.75	19.1	0.37	9.35	0.035	0.90
HS2SR-100	AMS-DTL-23053/5-110 and 310	1"	1.00	25.4	0.5	12.7	0.039	1.00