



A division of CSA Technical Solutions, LLC
1959 Hammondville Road, Pompano Beach, FL 33069
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Small Heat Shrink Tubing Adhesive Lined Kit

Features:

- Small Kit #2 (with adhesive)- 62 pieces of 3:1 Adhesive lined (dual wall) heat shrink in a polypropylene compartment storage box with hinged lid
- Kit contains the following (all pieces are 3-1/2 inch length):
- 1/8" – 20 pcs
- 3/16 – 20 pcs
- 1/4 - 10 pcs
- 3/8 – 5 pcs
- 1/2 - 5 pcs
- 3/4 - 2 pcs
- Operating Temperature: -55° C to 135° C
- Shrink Temperature: 120° C
- Shrink Ratio: 2 to 1
- Longitudinal Shrinkage: 5-10%
- Black is UV resistant

Specifications/Approvals:

Military: AMS-DTL 23053/5 Class 1 and Class3 (Clear = Class 2) (Formerly Mil- I-23053/4)

Underwriters Lab: UL 224 600V, 125°C, VW-1. CSA C22.2 RoHS, REACH compliant

Crosses to: Sumitomo B2, Raychem RNF-100, Alpha FIT-221, 3M FP301, FP301V, Canusa CPX-100, LG GSHS-1635F

Part Number	HSKIT-A-SM
--------------------	------------