



A division of CSA Technical Solutions, LLC
1980 NW 44th St Deerfield Beach, FL 33064
Phone 954-978-0056 Fax 888-617-2010
www.BuyHeatShrink.com

Ultra Thin Wall Heat Shrink Tubing 2:1 Ratio

Features:

- Lower shrinking temperature than [PVC](#), and higher use temperature
- Ultra Thin wall for confined/tight spaces
- 2:1 Shrink Ratio (shrinks to ½ its original diameter)
- UL 224 VW-1 300V and CSA OFT 150V recognized
- Maximum Continuous use temperature 125°C
- Standard color: Black
- Shrink Temperature of 100°C and operating temperature of -55°C to + 125°C
- Crosses to: Sumitomo F4, Raychem Versafit V4 (Versathin), LG GSHS-1635T
- Typical applications include: Insulation, Wire Identification, Wire Bundling, Mechanical Protection, Lightweight Harnessing, Physical/Electrical Protection of Components, Strain Relief, and Solder Insulation.

Dimensions

Part Number	Nominal ID	Flattened Width	After Shrinking	
			ID	Wall
HS2T-0047	3/64"	1/16"	0.023"	0.007
HS2T-0063	1/16"	1/8"	0.031"	0.007
HS2T-0094	3/32"	1/8"	0.047"	0.007
HS2T-0125	1/8"	3/16"	0.063"	0.007
HS2T-0188	3/16"	5/16"	0.094"	0.010
HS2T-025	1/4"	3/8"	0.125"	0.010
HS2T-0375	3/8"	9/16"	0.188"	0.011
HS2T-050	1/2"	13/16"	0.250"	0.011
HS2T-075	3/4"	1-3/16"	0.375"	0.016
HS2T-0787	7/8"	1-1/4"	0.394"	0.016
HS2T-100	1"	1-9/16"	0.500"	0.016